


UL316RS-27

27W (9 X 3W) - 12VAC or 24VDC
Submersible or Dry
Replaceable LEDs
Cast 316L SS



Specifications

| | |
|----------------------|--------------------------------------------------------------------|
| Input voltage | 12VAC or 24VDC |
| Output power | 27 watts (9X3W) |
| Luminous flux output | 100 to 110 lm/W |
| Rendering Index | >70rA (warm white) |
| Beam angle | 10-15 degrees - optional 25,45,60,90(25° for RGBW) |
| LEDs | Replaceable - Internal Driver |
| Material | Cast 316L STAINLESS STEEL silicone gasket - tempered glass lens |
| Face ring | Standard 'sparkle matt' SS |
| Color options | RGB-DMX, RGBW, RGBWW |
| White | CREE- XPE - 2700K TO 6500K |
| LEDs operating life | > 50,000 hours REPLACEABLE LEDs |
| IP rating | IP68 - CERTIFIED SUBMERSIBLE OR DRY |
| Cable | 9 FEET- SOW 18/5 - longer lengths can be ordered |
| Dimensions | Diameter 9.8" x 2.3" |
| Certifications | cULus CSA22.2 no.89 - including swimming pools and splash pads |
| Installation | Submersible or Dry |

